

5000-PM-NI-PS/2 - NON-INCENDIVE PANELMOUNT KEYBOARD



Sealed Non-Incendive Safe Keyboard, w/ Built-in Mouse

- Environmentally Sealed to NEMA 4, 4X / IP65 specifications when properly installed.
 - Panelmount Stainless Steel Case
 - Includes Bulkhead Connectors
 - 114 Keys, 20 Function Keys, WIN KEY
 - Built-in 3 button Pointing Device
 - Greater than 10 Million cycles expected life
- Includes separate PS/2 cables with Bulkhead connectors
(If you have a requirement please [contact us](#) for availability.)



PRODUCT DESCRIPTION

Stealth Computer manufactures a full line of non-incendive keyboards and pointing devices. Each unit is enclosed in a stainless steel case and carries a Factory Mutual approval of Class I, Division II. These units do not require barriers and are ideal for harsh working conditions. All units ship with bulkhead cables.

ADDITIONAL INFORMATION

Industrial Approvals

FM Approved for Class I, II, III
Division II, Groups: A, B, C, D
NEMA 4, 4X, IP65* when properly installed, UL/ULc 60950, CE, FCC
Class 15, Part B

* Proper instructions must be followed to create a water-tight seal
(NEMA 4X / IP65)

Material: Industrial Silicone Rubber

Life: Greater than 10 million cycles

Travel: 0.060" (1.5mm)

Actuation Force: 5oz (130g)

Feedback: Tactile with mechanical snap

Key Switch

Mouse: 5V@10ma (from mouse conn. port)

Keyboard: 5V@10ma (from CPU Port)

Power

Temperature Range

-40C to +90C (-40F to +194F)

Humidity

100%

Shock

3x11 ms pulses of 50g on each of 3 axes

Vibration

Power Spectral Density: 0.04g/Hz, Frequency Range: 20Hz-2kHz,
Duration of Test per Axis: 3 hours

Dimensions

(W-H-D) 17.7" x 9.2" x 2.0" (449.6mm x 233.7mm x 50.8mm)
CUTPIT: 16.4" x 7.9" (416.56mm x 200.66mm)

Cable

Length: 5 feet from keyboard to Bulkhead Connector

Design: separate cables

(providing separate keyboard and mouse connections)

Compatibility

Compatible with all Windows Operating Systems

Warranty

1 Year limited Warranty Standard

Model Numbers

5000-PM-NI-PS/2 (PS/2 Interface)

Disclaimer

Note: Specifications are subject to change without notice.