



19" RUGGED DESKTOP INDUSTRIAL LCD MONITOR (TT-1905)




\$2,095.00 USD

Model: TT-1905

- 19" Rugged Metal Enclosed Industrial LCD Monitor
 - NEMA 4, IP65 - Sealed front panel
 - Resistive or Capacitive Touch Screen Options
 - Supports 100mm VESA Mounting
 - Wide range DC input (9 - 36V DC)
 - Wide Operating Temp (-10C - +60C)
- Ideal for use in industrial and commercial environments
 - 3 Year Warranty



GALLERY IMAGES



PRODUCT DESCRIPTION

Stealth's TT-1905 is a 19" Rugged Touch Screen Industrial LCD Monitor designed to deliver performance and reliability that is ideally suited for industrial and commercial environments.

This Industrial LCD Display is available with resistive or capacitive touch screen options and includes support for wide range DC input (9 - 36V DC) and extended operating temperature of -10C - +60C (14F - 140F).

The TT-1905 comes standard with a 3 Years Warranty and also features rear VESA 100mm mounting allowing it to be connected to a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Prior to shipping, each and every display is put through Stealth's rigorous QA burn-in procedure that is documented and controlled through our ISO 9001 quality system.

In addition to our Rugged Desktop Displays, Stealth offers a [wide range of LCD product](#) offerings that include Panel mount, Rack mount and Open Frame designs as standard off-the-shelf products in 8.4" up to 24" diagonal sizes.

ADDITIONAL INFORMATION

Weight	N/A
Screen Size	19.0" (Diagonal)
Aspect Ratio	5:4
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)
Pixel Pitch	0.294mm x 0.294mm
Response Time	10ms (Typical, On/Off)
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	VGA / HD-15 DVI Compliant Digital HDCP (DVI-D) HDMI
Viewing Angle	170° / 160° (H / V) - (Viewing angle of LCD panel without touch)
Contrast Ratio	1000:1 (typical)
Luminance (Brightness)	350 cd/m2 typical at center (350 Nits)
Viewable Image Size	Horizontal: 14.816" / 376.32 mm, Vertical: 11.853" / 301.056 mm
Input	AC Adapter is Removable DC Input: 9V - 36V DC AC Input: 100-240V, 50-60Hz, 1.5A
Control Buttons (Rear mounted)	Power, Left, Right, Menu
Controls On-Screen Display	Brightness, Contrast, Input Source, Color, Image Adjust, OSD Lockout
LCD Mounting Options	Rear VESA 100mm Mounting Front bezel only
Environmental Rating	Meets NEMA 4 / IP65 Protection against windblown dust, rain, splashing water, and hose-directed water

Environmental

Operating Temperature: -10C - +60C (14F - 140F)
Storage Temperature: -30C - +85C (-22F - +185F)
Operating: Relative Humidity 20% ~ 80%
Storage Relative Humidity: 20% ~ 80%

Panel Finish

Black Powder Coated

Unit Weight

Shipping Weight: 19 Lbs (8.62 Kg)
Unit Weight: 17.55lbs (7.96Kg)
* Weight may vary depending on configuration

Dimensions

18.45" x 14.56" x 2.68" (468.63mm x 369.83mm x 68.07mm)
Without Mounted Power Supply: 18.45" x 14.56" x 4.09"
(468.63mm x 369.83mm x 103.89mm)

Available Models

TT-1905-RT - Resistive (USB and Serial / DB9)
TT-1905-CT-DB9 - Capacitive (Serial / DB9)
TT-1905-CT-USB - Capacitive (USB)

Warranty

3 Year Parts and Labor

Disclaimer

Note: Specifications are subject to change without notice.