

MODEL

DESCRIPTION

LPC-401PCI Small FootPrint Pentium 4 Little PC with PCI slot expansion



With a PCI Expansion Slot

Features:

- Full Featured Small PC in the Palm of your Hand
- POWERFUL Pentium 4 & Celeron processors
- **PCI Slot - Support 1xPCI card**
- 2D/3D AGP VIDEO w/16x9 Capability
- LAN, USB, Firewire, Audio, Serial, Video - All On Board
- Rugged Extruded Aluminium Chassis - takes Vibration, Shock & Heat
- Built-in CD-ROM or optional DVD or CD/RW
- Solid State Hard Drives (Flash) optional
- WINDOWS Compatible, **other O/S Options Available*
- **Dimensions:** 10" x 5.82" x 2.79"

LPC-401PCI Specifications

- **Processor**
Intel Pentium 4 & Celeron processor 2.0 Ghz
- **Chipset**
Intel 865GV / ICH 5(North / South)
FSB support up to 800Mhz
- **Memory**
Support Dual-Channel DDR 400/333/266
Uses 0.8" low profile, 1GB Max
- **Hard Disk Drives, IDE internal**
2.5" Hard Drive, 30, 40, 60, 80GB UltraDMA 100
- **PCI Slot**
Support 1xPCI card and length up to 24cm
PCI 2.1 Compliant
Supports 3.3V and 5V PCI cards
- **CD-ROM**
24X Standard, Slim Style,
Optional: Slim DVD-ROM, DVD/DVDRW, CD-RW
- **Video**
Intel Extreme Graphics 2
Support up to 64MB DVMT video memory
- **Cooling Fans**
Internal thermal controlled CPU only
- **Power Input**
+ 12VDC (mini-jack input)
Includes AC Adapter,
Input 100~240V AC Universal Output 12V DC power adapter
- **Options**
Flash IDE Hard Drives
Wall Mount Bracket
USB Key (mini-Flash drive) for easy file transfer
- **Back Panel**
- 2 x RS232 COM port, parallel printer port
- 1 x RJ45 10/100Mb Fast Ethernet
- 1 x Line-Out output Jack
- 2 x USB 2.0 / 1.1 Ports
- 1 x 15 pin VGA, 12v DC Power Jack input
- **Front Panel**
- 1x IEEE 1394 Firewire port
- 1x USB 2.0 / 1.1 Port
- 1x MIC Port, Ear Phone output Jack
- 1x Power-on button
- 1x Reset button
- 1x Power-on and HDD LED

- **Ethernet Port**
Ethernet 100/10Mbps LAN controller, RJ-45 connector
- **Audio**
Software AC 97 Audio CODEC, 1-line-out, 1-Mic-in, 1-Earphone
- **Operating Systems**
WINDOWS Compatible
*Optional: Windows 2000, Linux, QNX & embedded.
- **Power Management**
ACPI 1.0b compliance and OS direct power management
Wake-on-event:
RTC/USB/Keyboard/Modem/Keyboard/Mouse
- **Hardware Monitor**
System, processor temperature, voltage and fan speed
monitor Auto Thermal FAN speed control
- **Chassis Description**
Ultra light extruded Aluminum
Power on, reset buttons with power on and HDD LED's
- **Dimensions**
10.0" x 5.82" x 2.79" or (25.4 x 14.8 x x 7.1 cm) L x W x H
- **Environmental**
 - Operating Temperature: 0-40C
 - Non-Operating Temperature: (Storage) -20~60C
 - Operating RH (non condensing) 10-80%
 - Non Operating RH (non condensing) 0-90%
- **Shipping Weight**
< 6.0 lbs. Or 2.4KG (Depending on configuration)
- **Warranty**
1 Year

