

Features:

- **17" Rugged Metal Enclosed Industrial LCD Monitor**
- NEMA 4, IP65 - Sealed front panel
- Resistive Touch Screen
- Versatile VESA Mounting Options
- 17.0" Active Display Area
- Wide Viewing Angles, 176° (H) / 170° (V)
- Ideal for use in industrial and commercial environments
- 2 Year Warranty
- **Now with integrated Little PC option**
- Other sizes & options available.
Minimum quantities may apply.



(shown with optional bench/desktop stand, click on images for larger pictures)

TT-1700 - Pricelist

Model: TT-1700 - TuffTouch
Metal Encapsulated Industrial Grade LCD Monitors

Finally a Rugged versatile Touch Screen LCD Monitor designed to stand-up to the rigors of industry. Stealth's TuffTouch LCD delivers performance and reliability that is ideally suited for industrial and commercial environments. TuffTouch is available with resistive touch screen option and includes a wide-range of versatile mounting options such as Wall, Bench top, Pendant Arm and Ceiling mounts.

Available with built-in Little PC. Our powerful small computers are integrated into the rear bracket of the TuffTouch LCD. In less than 1 minute Stealth's Small PC is installed with the easy-connect rear bracket. A simple and convenient way to upgrade service and install your application.

TT-1700 Specifications

Screen Size	17.0" (Diagonal)
Aspect Ratio	4:3
Native Resolution	1280 x 1024 (Auto sync from 640 x 480 to 1280 x 1024)


Horizontal Frequency	30 kHz ~ 83 kHz
Vertical Frequency	56 Hz ~ 75 Hz
Pixel Pitch	0.264mm x 0.264mm
Response Time	5ms Typical
Type	TFT Active Matrix Liquid Crystal
Video Input Connectors	Analog (VGA / HD-15), DVI Compliant Digital HDCP (DVI-D)
Viewing Angle	176° (H) / 170° (V) - (<i>Viewing angle of LCD panel sans touch/AR glass</i>)
Contrast Ratio	800:1 (typical)
Luminance (Brightness)	250 cd/m2 typical at center (250 Nits)
Viewable Image Size	Horizontal: 13.3" / 337.9 mm Vertical: 10.6" / 270.4 mm
Video Signal	ANALOG: 0.7 Vp-p/75 Ohms
Sync Signal	Separate Sync, Composite Sync, Sync on Green, (Positive/Negative)
Operating Temperature	0 - 40C (32 to 104 F) Humidity 20% ~ 80%, non-condensing Altitude Sea Level to 12,000 ft
Storage Temperature	-20C - 60C (-4 to 140 F) Humidity 20% to 80%, non-condensing Altitude Sea Level to 40,000 ft.
Input	AC Input: 100-240 V ~ 50/60 Hz, 0.7A @ 100-120VAC, 0.36A @ 220-240VAC
Control Buttons (Rear mounted)	Left (-), Right (+), Up, Down, Auto Adjustment, Brightness Hot key, OK, Power ON/OFF
Controls On-Screen Display	Brightness, Contrast, Auto Adjust, Image Position, Image Adjust, Color Adjust, Display Mode, Language Select, OSM Lockout, OSM Time-out
Environmental	NEMA 4 / IP65 Front Panel protection against windblown dust and rain, splashing water, and hose-directed water

Panel Finish / Enclosure	<ul style="list-style-type: none"> - Black Baked Enamel - Aluminum Alloy - 100mm VESA Rear Mount
Unit Weight	Unit 25.05 lbs (11.36 Kgs)


Available Models:	<p>TT-1700 - Protective Anti-Reflective Glass</p> <p>TT-1700-RT-SERIAL - Resistive Touch with Serial/DB9 Interface</p> <p>TT-1700-RT-USB - Resistive Touch with USB Interface</p>
- NEMA 4 / 4X sealed when properly installed	

Dimensions	<p>Standard Config: 16.52" x 13.48" x 3.51" 419.73mm x 342.51mm x 89.28mm</p> <p>With Optional Mounting Bracket for LittlePC: 16.52" x 13.48" x 5.8" 419.73mm x 342.51mm x 147.32mm</p>
------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------


LCD Mount Options




Ceiling Mount




Wall Mount



Fixed Mount



Wall Mount



LittlePC Mounted

For more information and pricing on mounts please contact us.

Additional Options	<ul style="list-style-type: none"> - Various VESA Mount Brackets - Little PC Rear Mount Option - Other sizes & options available. <p><i>Minimum quantities may apply.</i></p>
--------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Included Accessories	<ul style="list-style-type: none"> - AC Power Cord - VGA Cable - Touch Screen Driver CD
----------------------	--------------------------------------------------------------------------------------------------------------------------

Product Bundle	Bundle with a Stealth LittlePC or Panelmount Computer and Save
----------------	----------------------------------------------------------------

- see pricelist links above for more details

Warranty

2 Year Parts & Labor

NOTE: Specifications subject to change without notice.