

## Datasheet

### Models: 79-SK (PS/2 or USB)

(Small Footprint NEMA 4, 4X, IP65 keyboard, w/ Built-in Mouse)

The Stealth Computer model 79-SK have been designed for those mobile applications when a small-footprint keyboard will come in handy. Featuring an integrated HulaPoint II pointing device with dual left-click capability, the NEMA 4X-rated 79-SK offer a large amount of functionality in an ultra-small package. Like other keyboards in the Stealth Computer line, the 79-SK feature sealed, industrial silicone rubber keypads, as well as robust ABS polycarbonate cases. The standard 79-SK measures only 1" inches deep. The optional Mobile version is 1.68 inches deep and features mounting holes in its case.

### Product Photo



(click on image for a larger picture)

### Keyboard Features

- **LOW COST** NEMA 4, 4X, 12, IP65
- ABS-Polycarbonate Sealed Plastic Case
- Small Foot Print Design
- 79 Keys, 12 Function Keys, WIN KEY, Built-in HULA Pointing Device
- 10 Million cycles expected life
- Includes 3' cable w/ PS/2 cables or USB connector
- Optional Mobile Mounting
- Other Languages Available
  
- Dimensions:  
9.27"W x 3.87"D x 1.0"H (standard)  
9.31"W x 3.88"D x 1.68"H (mobile)

### Ordering Information

### Technical Information

### Technical Specifications

- **Industrial Approvals**  
Nema 4, 4X, IP65  
UL/ULc 60950, CE, FCC Class 15, Part B
- **Key Switch**  
Material: Industrial Silicone Rubber  
Life: Greater than 10 million cycles  
Travel: 0.055" (1.4mm)  
Actuation Force: 4.76oz (135g)
- **Vibration**  
Power Special Density: 0.04g/Hz  
Frequency Range: 20Hz-2kHz  
Duration of Test per Axis: 3 hours
- **Dimensions**  
(W-H-D) 9.27" x 3.87" x 1.0" (standard)  
235.5mm x 98.3mm x 22.9mm  
(W-H-D) 9.31" x 3.88" x 1.68" (mobile)

Feedback: Tactile with mechanical snap

236.5mm x 98.6mm x 10.9mm

- **Power**

PS/2 Keyboard: 50mA @ 5V (from keyboard Port)

PS/2 Mouse: 35mA @ 5V (from mouse port)

USB Keyboard / Mouse: 85mA @ 5V from USB port

- **Temperature Range**

-40F to +194F (-40C to +90C)

- **Humidity**

100%

- **Shock**

3x11 ms pulses of 50g on each of 3 axes

- **Flammability**

Printed Circuit Board: 94 VO

Silicone Overlay: 94 HB

Interface Cable: 94 VO

- **Cable**

Length: 3 feet (0.9 meters)

Design: "Y" PS2 (providing separate keyboard and mouse connections), or Single Cable USB

- **Compatibility**

PS/2 & USB Keyboard:

Compatible with all Windows Operating Systems

- **Other Languages Available**

- **Warranty:**

1 Year Limited Warranty

- **Model Numbers**

79-SK-PS/2 (PS/2 Interface)

79-SK-USB (USB Interface)

79-SK-M-PS/2 (Mobile version, PS/2 Interface)

79-SK-M-USB (Mobile version, USB Interface)

*NOTE: Specifications subject to change without notice.*